

## EFA-SST® Premium: The energy-saving door

The EFA-SST® Premium impresses customers all over the world through its outstanding quality, great aesthetics and extreme operating capacity. Incredible attention to technical details like our EFA-THERM® laths or the sealing mechanism ensures unrivalled sound and thermal insulation values.



### Spiral design

- Extremely fast and quiet operation due to our spiral construction
- Designed to minimise contact, reducing abrasion to the door blade and glazing
- Round and oval spiral versions available

### Door blade

- Thermally separated and insulated EFA-THERM® laths as standard
- Reducing energy costs with U values up to 0.66 W/m<sup>2</sup>K (depending on door size)
- Transparent laths (double-walled or single-walled) available with acrylic or polycarbonate infills

### Control EFA-TRONIC®

- Externally mounted polycarbonate control box
- With integrated frequency converter

### Finish

- Galvanised, stainless steel or powder coating acc. to RAL

### Safety

- Infra-red light curtain (EFA-TLG®) as standard
- Locking handle as standard

### Manual release

- Manual opening utilizing spring tension

### Speed/Cycles

- Opening speed up to 2.5 m/s (depending on door size)
- 250.000 operating cycles per year

### General

- Max. sizes W = 8,000 mm x H = 8,000 mm
- Wind class 2 – 4 (depending on door size)
- Tested and certified by IFT institute

